



UNIVERSAL ROBOTS

A Teradyne Robotics Company


Gen 7 Cables

Generation 7

Technical Data Sheet

Updated September 2026

Copyright © 2026 by Universal Robots A/S. All rights reserved.



Robot cable specification

Description

The g-Series, e-Series, and UR20/30 robot cable connects the robot arm to the CB7 Control Box and provides power, control, and high-speed communication. It includes an integrated Ethernet connection and Harting connectors, and supports cable lengths up to 12 m. Available in standard or drag chain variants.

Robot Cable

Description

Standard lengths	6 m, 12 m
Outer material	PU, PUR, or TPU
Diameter (standard cable)	13.8 ± 0.8 mm
Diameter (chain cable)	16.5 ± 0.4 mm
Connector type	Harting ICC20 series
Robot arm cable end connector	Harting Receptacle
Control box cable end connector	Harting Plug
Ethernet	100/1000 Mbps
Mating cycles	500

Teach Pendant Cable

Description

Teach Pendant port	ethTP (Ethernet)
Connection	TP7 to CB7 via dedicated Teach Pendant port

Compatibility

Robot arms	g-Series, e-Series, UR20/30 CB7 Core
Controller	CB7 Core Compact CB7 Core Compact 0.55m

Contact

UR HQ address

UR HQ phone

UR email

UR website

Universal Robots A/S
Energivej 51
5260 Odense, Denmark
+45 89 93 89 89
sales@universal-robots.com
universal-robots.com



UNIVERSAL ROBOTS

A Teradyne Robotics Company


Gen 7 Cables

Generation 7 · g-Series 01


Technical Data Sheet

Updated September 2026


Copyright © 2026 by Universal Robots A/S. All rights reserved.




Harting connector alignment



Robot cable connection to Control Box



Robot cable at base flange



UNLESS OTHERWISE SPECIFIED: Dimensions are in millimeters.

September 2026

Contact

UR HQ address

UR HQ phone

UR email

UR website

Universal Robots A/S
Energivej 51
5260 Odense, Denmark
+45 89 93 89 89
sales@universal-robots.com
universal-robots.com